

2425.0

Q 10

Q 10



M2.5 

Cross-connector, No. of poles: 10, Mounting type: Can be screwed on, Width: 49.9 mm, Rated cross-section: 2.5 mm<sup>2</sup>, Colour: natural

## Business data

Product description	Cross-connector
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	8.16
Weight per piece (including packaging)	8.2
Unit of weight	G
Customs number	85389099
Country of origin	DE

2425.0

Q 10

Q 10

## Technical Data

---

### Dimensions

---

Length	4 mm
Width	49.9 mm
Hole height	2.5 mm
Hole diameter	2.8 mm
Hole spacing (mid-point to mid-point)	5.1 mm
Pitch size	5 mm
Slotted hole	✓

### Ratings

---

Voltage with partition, max.	400 V
Voltage without partition, max.	400 V
Rated current	20 A
Rated cross-section	2.5 mm <sup>2</sup>
Contamination degree	3

2425.0

Q 10

Q 10

## Technical Data

---

### Connection data

---

No. of poles	10
Screw head	Slotted
Screw threading	M 2,5
Tightening torque, min.	0.4 Nm
Tightening torque, max.	0.8 Nm

### Materials

---

Material	Copper
Surface	Tin-plated
Surface screw	Galvanized

### Further technical data

---

Mounting type	Screwable
Number of bridged terminals	10

2425.0

Q 10

Q 10

Media

---

**M2.5**



2425.0

Q 10

Q 10

## Accessories

---

### Screw driver

---



Screwdriver with bare blade, Colour: Black-grey

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
1086.0	SDB 0,6x3,5	4044211014797	1 PC

---