

Junction box

Abox SL-16²



Abox SL-16²

Junction box

CUSTOMIZABLE

Productnumber: 83581001
Dimensions: 250 x 200 x 115 mm

Junction box acc. to DIN EN 60670 (VDE 0606),
Ui=690V, with IP54 attachment bushes, M40,
seal range 17 - 30 mm, with blanking plug M40,
with sealing kit

Grey, with 5-pole high-set screwless terminal, max. cross-section acc. DIN EN 60998: 16 mm², for current carrying capacity of 76 A, cross sections that can be clamped per pole: 4 x 0.5 up to 16 mm², rigid, 4 x 0.5 up to 25 mm² flexible



To industrial product:
<https://www.spelsberg.com/p/49083501>

Technical Data

electrical characteristics

Protection type UL:	not specified
Rated insulation voltage AC:	690 V
Type of protection:	IP54/IP65
Circuit integrity class:	none
Max. conductor cross section:	16 mm ²
Protection class:	II

Colours

Cover colour:	grey
---------------	------

Dimensions

Length:	200 mm
Width:	250 mm
Height:	115 mm

Material characteristics

suitable for exterior use:	no
Halogen free:	yes
Industry quality:	no

mechanical properties

Type of fastening:	Wall/ceiling mounting
Sealable:	yes
Cover screw torque:	1 Nm
Impact strength:	IK07

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25
Max. ambient temperature:	40
24h ambient temperature:	35

Material

Base unit material:	Polystyrene
Cover material:	Polystyrene
Cover screw material:	Stainless steel V2A

Certificates

Test mark:	VDE
------------	-----

Accessories

WST M20 - Twist plug

WST M25 - Twist plug

WST M32 - Twist plug

WST M40 - Twist plug

WNI M20 - Twist nipple

WNI M25 - Twist nipple

WNI M32 - Twist nipple

KVR M20-MGM - Cable gland

KVR M20-GDB/MGM - Cable gland

KVR M25-MGM - Cable gland

KVR M32-MGM - Cable gland

KVR M40-MGM - Cable gland

VST M20 - Sealing plugs

VST M25 - Sealing plugs

VST M32 - Sealing plugs

VST M40 - Sealing plugs

DMS M20/w - M20, white

DMS M25/w - M 25, white

DMS M20 - Double-membrane seals

DMS M25 - Double-membrane seals

DMS M32 - Double-membrane seals

DMS M32/4 - Double-membrane seals

DMS M40 - Double-membrane seals

BST M20/sw - Ventilation seal

BST M20 - Ventilation seal
