

Junction Box

# Abox-i 060-L/sw

## Abox-i 060-L/sw

Junction Box

**CUSTOMIZABLE**

Productnumber: 49190601  
Dimensions: 110 x 110 x 67 mm

Junction box - Industrial Quality - acc. to DIN EN 60670 (VDE 0606),  $U_i=690V$ , weatherproof, shock-proof, halogen-free, with IP66 double-membrane seals, M25, seal range 9 - 16 mm

**black, without terminal**



## Technical Data

### electrical characteristics

Protection type UL:	not specified
Rated insulation voltage AC:	690 V
Type of protection:	IP65
Circuit integrity class:	none
Max. conductor cross section:	6 mm <sup>2</sup>
Protection class:	II

### Colours

Cover colour:	black
---------------	-------

### Dimensions

Length:	110 mm
Width:	110 mm

### Dimensions

Height:	67 mm
---------	-------

### Material characteristics

suitable for exterior use:	yes
Burning behaviour in accordance with UL 94:	5VA
Burning behaviour in accordance with VDE:	650
Halogen free:	yes
Industry quality:	yes

### mechanical properties

Type of fastening:	Wall/ceiling mounting
Sealable:	yes
Cover screw torque:	1.7 Nm
Impact strength:	IK08

## Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35
Max. ambient temperature:	80
24h ambient temperature:	60

## Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate, glass-fibre reinforced
Sealing material:	Polyurethane
Cover screw material:	Stainless steel V2A

## Certificates

Test mark:	VDE
Test mark:	DLG
Test mark:	DNVGL
Test mark:	VDE DIN EN 60670-1/-22 (VDE 0606-1/-22)
Test mark:	DLGA
Test mark:	DNVGLS

## Accessories

---

KS M25 - Combi set

---

KS M25-gro - Combi set

---

KVR M20-MGM/sw - Cable gland

---

KVR M25-MGM/sw - Cable gland

---

DMS M20/sw - Double-membrane seals

---

DMS M25/sw - Double-membrane seals

---

BST M20/sw - Ventilation seal

---

BST M20 - Ventilation seal

---

Abox 060 KLS-6<sup>2</sup> - Terminal block

---

Abox PST - Sealing kit

---

Abox 060 MPI - Mounting plate

---